




UK HEALTH & SAFETY POLICY

(Including Generic Risk Assessments)

DOCUMENT APPROVAL & REVISION HISTORY

Rev.	Status	Author(s)	Reviewed By	Approved By	Issue Date
001	Active	Adrian Hanna, Safety Officer	Barry Glavin Area Manager	Aidan O'Mahony Managing Director	10 th May 2024

Signed By	 Managing Director	Date	10th May 2024
-----------	--	------	---------------

Index

1. Introduction	4
1.1 Health & Safety Policy Statement	4
2. Health and Safety Rules & General Arrangements	5
2.1 Training and Information.....	5
2.2 Identification of Training Needs.....	5
2.3 Specific Training	5
2.4 Training Records	5
2.5 Information.....	5
2.6 Safety Consultations and Safety Representative.....	5
2.7 Safe Systems of Work.....	6
2.8 Working at Heights.....	6
2.9 Hazards Audits	7
2.10 Occupational Driving	7
2.11 Smoking, alcohol & drug use.....	8
2.12 Use of Mobile Phone	8
2.13 First Aid	8
2.14 Manual Handling.....	9
2.15 Working on sites still under Construction	10
2.16 CSR & CSCS (Construction Skills Certification Scheme)	10
2.17 Non-Employees.....	10
2.18 Contractors/Sub-Contractors	10
2.19 Personal Protective Equipment (PPE).....	10
2.20 Accident /Incident Report and Investigation	11
2.21 Pregnant Employees.....	12
2.22 Stress Management	13
2.23 Bullying, Harassment &Sexual Harassment	14
2.24 Emergency Evacuation Procedures - Fire, bomb, and any other emergency.....	14
3. Risk Assessments.....	15
3.1 Identification of all hazards	15
3.2 Evaluation and measurement of the risk	15
3.3 Implementation of measures to eliminate or control risks.....	15

3.4	Risk and Hazard Definitions	15
3.5	Review of the risk assessment	15
4.	Completed Risk Assessments	16
4.1	Access / Egress	16
4.2	Compressed Air	16
4.3	Biological Agents	17
4.4	Chemical Agents.....	20
4.5	Dust.....	22
4.6	Confined Spaces	22
4.7	Electrical Installations.....	23
4.8	Fire	23
4.9	Housekeeping	24
4.10	Manual Materials Handling	24
4.11	Pressure.....	25
4.12	Temperature	25
4.13	Tools and Equipment.....	26
4.14	Visual Display Equipment	26
4.15	Noise	27
4.16	Working from Home and Temporary Workstations	28
5.	References	29

1. Introduction

This Health & Safety Policy provides the framework setting of the manner in which the organisation manages safety and health throughout Hanley Calibration.

This Health & Safety Policy is formulated in compliance with the Health and Safety at Work Act 1974, the Fire Precautions (Workplace) Regulations 1997, the Management of Health and Safety at Work Regulations 1999. It is prepared in writing; it consists of a safety policy specifying the manner in which health, safety and welfare is secured at the workplace. This safety statement is based on a risk assessment identifying hazards and assessing the risk to safety and health and the implementation of control measures to secure safety and health at work.

This safety statement specifies the general arrangements and resources provided for maintaining health and safety for employees, contractors, and relevant others of the company. The names and titles of persons responsible for securing health and safety are identified in the safety statement.

1.1 Health & Safety Policy Statement

Hanley Calibration recognises and accepts its health and safety duties for providing a safe and healthy working environment for all its workers (paid or volunteer) and other visitors to its premises under the Health and Safety at Work Act 1974, the Fire Precautions (Workplace) Regulations 1997, the Management of Health and Safety at Work Regulations 1999.

The managing director has overall responsibility for the implementation of the safety management system, modifications and changes to the safety statement, in consultation with employees and safety representatives.

All managers and supervisors are responsible for the safety and health of employees in their charge to the managing director. It is essential to the implementation of this policy that all employees read it and understand their role in maintaining health and safety. It is the policy of Hanley Calibration to adhere to their legal obligation of the Health and Safety at Work Act 1974, the Fire Precautions (Workplace) Regulations 1997, the Management of Health and Safety at Work Regulations 1999. in so far as is reasonably practicable in ensuring the following:

- The design, the provision and Management of a place of work in a condition that is safe and without risk to health.
- The design, the provision and the Management of access to and egress from place of work.
- The design, the provision and the Management of plant and machinery that are safe and without risk to health
- The provision of systems of work that are planned, organised, performed and maintained so as to be safe and without risk to health. This is outlined in the Hanley Calibration Quality Manual.
- The provision of such information, instruction, training and supervision as is necessary to ensure the safety and health at work of its employees
- In circumstances in which it is not reasonably practicable for Hanley Calibration to control or eliminate hazards in a place of work under their control, or in such circumstances as may be prescribed, the provision and Management of such suitable protective clothing or equipment, as appropriate, that are necessary to ensure the safety and health at work of its employees
- The provision and the Management of facilities and arrangements for the welfare of their employees at work.
- The safety statement is revised and updated as required and annually by a delegated competent person.
- The current safety statement is issued to all employees.
- The company is committed to obtain any pertinent safety information from its clients. This is detailed in Hanley Calibration Quality Procedure DP6 Service Provision.
- The company is committed to complying to with the requirements, relating to stress, anti- bullying, harassment and sexual harassment, of the Health and Safety at Work Act 1974, the Fire Precautions (Workplace) Regulations 1997, the Management of Health and Safety at Work Regulations 1999.

2. Health and Safety Rules & General Arrangements

2.1 Training and Information

Health and safety training is provided to all employees at Hanley Calibration. In compliance with the preventative approach of The Management of Health and Safety at Work Regulations 1999.

2.2 Identification of Training Needs

Training needs of employees are identified at induction and reviewed annually at their staff appraisal and at management review meetings.

2.3 Specific Training

Specific safety and health training is provided to employees involved in activities as in the relevant sections of the safety statement.

This includes:

- Manager responsibilities
- First aid
- Use of fire-fighting equipment
- Use of Personal Protective Equipment
- Risk Assessment
- Emergency Procedures
- Evacuation Drill
- Confined Space
- Working at Heights
- Mobile Elevated Work Platforms (MEWPs)
- Lock Out Tag Out

2.4 Training Records

The Training or Quality Manager maintains a record of each employee's safety training and certificates acquired on file.

2.5 Information

Information is available to all employees on safety and health relating to the company's activities through the safety statement. The master copy of the safety statement will be retained in the head office (Cork) and will be made available to any employee, contractor or customer through the company web site who wishes to view it.

2.6 Safety Consultations and Safety Representative

Safety Consultation

The Managers will consult with their employees to ensure their health, safety, and welfare at work and to consider any representation that they may have in compliance with its obligation under The Management of Health and Safety at Work Regulations 1999. and other relevant health and safety legislation. The safety officer, managers and safety representative(s) are responsible for co-ordinating and assisting management in consulting with employees and providing appropriate information on all matters pertaining to safety, health, and welfare in Hanley Calibration Ltd.

Safety Representative

Employees can elect their own safety representative. If no names are sent forward for nomination, management can elect a safety representative(s) on the employee's behalf.

The safety representative is afforded the opportunity to make representation on matters of safety, health, and welfare at the work place to the management. The safety representative is given access to information that pertains to the safety, health and welfare of employees and the powers to investigate accidents and dangerous occurrences. The safety representative is given the opportunity to receive appropriate health and safety training. The safety representative is allowed to make representations to the HSE (UK) inspectors on health and safety matters. The safety representative is informed when an inspector from the Health and Safety authority HSE (UK) visits the premises. The safety representative will not suffer any disadvantage through discharge of these functions.

2.7 Safe Systems of Work

A safe system of work is defined as “the integration of people, machinery, and materials in a correct working environment to provide the safest possible working conditions”. The Management of Health and Safety at Work Regulations 1999. requires the provision and Management of plant and systems of work that are, so far as is reasonably practicable, safe and without risk to health. The manner by which the safety, health, and welfare of people at work is secured in the provision of the following:

- Safe machinery, plant, and equipment – Appropriate design and safety specification, management and cleaning of plant machinery and equipment.
- Safe environment – Good welfare facilities and safe access and egress, controls on lighting, temperature, ventilation, dust, and noise.
- Safe place of work – Safe structure of the workplace i.e., stability of buildings, soundness of floors.

2.8 Working at Heights

The Management of Health and Safety at Work Regulations 1999. set out the basic principles for safe work at heights for all sectors of employment. The regulations cover the key requirements with regard to preventative measures, equipment used, inspection, records, working conditions, etc.

Safe Ladders – All ladders including step ladders will be carefully selected for each task, be free from patent defects, be of correct length, be carefully tied, be set at the correct angle, and, where necessary, be footed. Ladders must be controlled and subject to frequent auditing to ensure fitness for use. All ladders must be tied, such that they will not slip or slide while in use.

- Ladder is angled correctly (1 in 4 or 75 degrees)
- 3 points of contact are maintained when working on the ladder
- Ladder is secured at the top and at the bottom by a second person (where possible)
- No overreaching or stretching while working on the ladder
- Ladder is checked before use for defects, e.g. missing or damaged rungs

Scissors Lift /MEWPs Can extend to significant height using hydraulic scissors movement, and can be used where scaffold platforms are not suitable. Selection must be based on suitability for the task, with particular attention given to the ground conditions, and that the manufacturer’s guidelines for safe use can be followed fully. Only competent and trained operators should control the movement of these.

2.9 Hazards Audits

Safety Auditing is an ongoing process aimed at ensuring effective health and safety management. It is a systematic examination of the company's activities. The purpose of these audits is to ensure the continued suitability, adequacy and effectiveness of the health and safety management system.

The Safety Officer will initiate the Safety Audits as per Hanley Calibration annual Safety Plan. A **minimum of one per year** is required. Safety Officer can be accompanied by the department managers/supervisors and/or safety representative.

The Safety Audits will concern themselves with all aspects of the operations and will take account of the following potential hazards

- Access/Egress problems including floors, steps roads and aisles etc.
- Electrical Safety.
- Lighting and ventilation
- Manual operations, ergonomics
- Handling and storage of chemicals
- Use of personal protective equipment
- Noise and vibration
- Heating
- Systems of work
- Maintenance operations
- First Aid
- Substances or atmospheres hazardous to health.
- Fire safety
- Housekeeping
- Exposure to Biological Agents

2.10 Occupational Driving

Under The Management of Health and Safety at Work Regulations 1999. Employees who drive as part of their employment have a duty to ensure that the vehicles are constructed, maintained, and used in a safe manner. All Car/Van drivers must have a current full 'Driving Licence'. Please reference '**Driving for Work Policy**' outlined in **Employee Handbook**

Management must provide the employee with training and instruction in:

Safe loading/unloading of goods (Manual Handling)

The risk of developing a lower back injury from incorrect lifting techniques is high in the case of loading/unloading equipment from the rear of Hanley Calibrations Services vans. This risk is partly due to the low ceiling of the van, which requires the employees to stoop and crawl into the rear of the vehicle. This causes the lumbar region of the spine to be bent in a posture, which puts excess strain on the muscles of the back. This condition can be aggravated by compound movements such as twisting of the trunk and extension of the shoulders and arms causing an increase in torque on the biceps and triceps and causing fatigue.

Long distance driving

Under The Management of Health and Safety at Work Regulations 1999. the employer has a duty of care to the employee to provide a safe place and safe system of work. Fatigue or tiredness can cause an infringement on this duty and can lead to an incident or accident. Management should encourage the policy of employees taking regular rest breaks when driving over a long distance

Ergonomics of safe driving

The term ergonomics refers to how an employee interacts with their work environment, in this case their van. Issues such as seating, isolation of front and rear compartments and clothing are important concerns. The safety cage/partition that divides the driving & storage areas must not be interfered with. In the interest of safety as well as comfort, the seat should be adjusted so that it provides maximum support of the back (especially the lower back) and the headrest should align with the back of the driver's head. The same applies for any passengers in the vehicle. This measure helps to reduce the risk of severe injury due to whiplash in the unfortunate event of a road traffic accident.

2.11 Smoking, alcohol & drug use

Smoking, taking alcohol or drugs is prohibited in all places of work.

2.12 Use of Mobile Phone

The driving a mechanically propelled vehicle while holding a mobile phone is prohibited by Hanley Calibration.

2.13 First Aid

The company will comply with the requirements of The Management of Health and Safety at Work Regulations 1999. in the provision of first aid training and facilities. In a case of a minor injury which would otherwise receive no treatment or which does not need treatment by a registered medical practitioner or registered general nurse, treatment of that minor injury; "occupational first-aider" means a person trained and qualified in occupational first-aid.

First Aid Training

First Aid training is carried out by a competent independent organisation. Occupational First Aid Certificates are in general valid for 3 years.

First Aid Facilities

First Aid boxes are kept fully stocked in accordance with the recommended guidelines from the HSE(UK). These will be made available at or near the point of use. Please ensure that you are aware of the location of First Aid boxes.

When supplies from the boxes/cabinet are used, the designated first aider restocks the boxes as appropriate. All employees are aware that in the event of an injury, it must be reported to their manager/supervisor and to a person trained in first aid. All injuries are to be reported by the completion of an **Accident Report Form (ARF-001)**.

2.14 Manual Handling

Definition

The Management of Health and Safety at Work Regulations 1999. defines “manual handling of loads” as means any transporting or supporting of a load by one or more employees and includes lifting, putting down, pushing, pulling, carrying, or moving a load, which, by reason of its characteristics or of unfavourable ergonomic conditions, involves risk, particularly of back injury, to employees.

Injuries associated with Manual Handling include:

Strains and Sprains resulting in back pain and other muscular skeletal injuries

Manual Handling Regulation

Hanley Calibration Services Ltd. will comply with their duty as required in The Management of Health and Safety at Work Regulations 1999. on Manual Handling as follows:

- a) Take appropriate organisational measures, or use the appropriate means, in particular mechanical equipment, to avoid the need for the manual handling of loads by employees,
- b) Where the need for the manual handling of loads by the employer’s employees cannot be avoided, take appropriate organisational measures, use appropriate means, or provide the employer’s employees with such means in order to reduce the risk involved in the manual handling of such loads, having regard to the risk factors.
- c) Wherever the need for manual handling of loads by the employer’s employees cannot be avoided, organise workstations in such a way as to make such handling as safe and healthy as possible, and:
 - I. taking account of the risk factors for the manual handling of loads specified assess the health and safety conditions of the type of work involved and take appropriate measures to avoid or reduce the risk, particularly of back injury, to the employer’s employees,
 - II. Ensure that particularly sensitive risk groups of employees are protected against any dangers which specifically affect them in relation to the manual handling of loads and the individual risk factors, having regard to the risk factors.
 - III. ensure that where tasks are entrusted to an employee, his or her capabilities in relation to safety and health are taken into account, including, in relation to the manual handling of loads by employees, the individual risk factors
 - IV. when carrying out health surveillance in relation to the manual handling of loads by employees, take account of the appropriate risk factors set out in Schedule 3

Without prejudice ensure that those of the employer’s employees who are involved in manual handling of loads receive general indications and, where possible, precise information on—

- (i) The weight of each load
- (ii) The centre of gravity of the heaviest side when a package is eccentrically loaded.

Manual Handling Training

A qualified instructor will provide training to all employees for whom manual handling tasks involve a significant risk, which cannot be avoided. All employees will receive a recognised manual handling training course. Refresher courses provided after **3 years**.

2.15 Working on sites still under Construction

The Management of Health and Safety at Work Regulations 1999. provides appropriate guidelines when working on sites defined as 'Under Construction'. When an employee starts work on a customer's site that is either still under construction or is under repair or maintenance, the employee should be aware of the inherent risks involved. Construction sites are one of the most dangerous work places in Ireland today. Hazards such as falls from heights, electrical hazards, and scaffold and excavation collapse are often not found in other areas.

- Extreme care and vigilance must be taken when entering, moving around, and exiting the site so as not to interfere with other contractor's work and associated hazards.
- As far as possible identify other hazards not directly associated with your work, which could pose as a risk to you.
- Report any unsafe practices to your supervisor.
- Do not use another contractor's tools or equipment.
- Wear the appropriate personal protective equipment (e.g., Hi-Viz vests, safety boots, goggles, bump hats etc) when necessary

2.16 CSR & CSCS (Construction Skills Certification Scheme)

A qualified instructor provides training to all employees who work on construction sites. All employees who work on construction sites receive a recognised CSR & CSCS training course.

2.17 Non-Employees

Non-employees refer to contractors/*sub-contractors*, visitors and relevant others who visit the company *or are sub-contracted to do work for the company*. The company will abide the requirements of the Management of Health and Safety at Work Regulations 1999. in providing information and training to contract employees.

2.18 Contractors/Sub-Contractors

Contractors carrying out work at or on behalf of Hanley Calibration Services Ltd. must adhere to the following rules and regulations:

1. Contractors/Sub-Contractors must carry appropriate insurance liability cover.
2. Contractors/Sub-Contractors are provided with a copy of the Safety Statement and are made aware of the company 'Accident Reporting System'(ARF-001) prior to commencing work, which must be read, understood, and signed by them.
3. Contractors/Sub-Contractors must observe the company's safety rules for contractors and perform their work in accordance with the terms of the Safety Statement.
4. Contractors/Sub-Contractors (where applicable) must submit their own Safety Statement and Risk Assessment prior to commencing work.
5. Contractors/Sub-Contractors will follow the terms of any 'permits to work' systems in force e.g. (hot work permit for welding etc.).
6. Contractors/Sub-Contractors must prove competence and submit a copy of any Qualifications for perusal. (A Medical Examination may also be required)
7. Contractors/Sub-Contractors to be added to Company Training Matrix to monitor and record any compulsory or specific training requirements- i.e., Manual Handling, Safe Pass etc.
8. Contractors/Sub-Contractors must adhere to company policies and are subject to our Disciplinary Procedures.

2.19 Personal Protective Equipment (PPE)

Personal Protective Equipment includes equipment worn and used by people at work to protect them from both general and specific risks. The company will only use PPE as short-term measure until a safe place strategy is implemented e.g. (guarding on a machine) a last resort, when all other protection strategies have failed.

Where people and vehicles cannot be physically separated, other measures will need to be put in place. Where people must work in areas with moving vehicles or have to work close to moving vehicles, the risk may be further reduced by using high visibility clothing to signal their presence.

High visibility clothing is a vital and necessary requirement in any workplace where a significant proportion of the work occurs near, in, on and around moving vehicles. It is also of critical importance for people working at night or in low-light conditions.

Selection of PPE

The company will comply with its legal duty in the selection and provision of PPE in accordance with The Management of Health and Safety at Work Regulations 1999.

Suitability of PPE

The Regulations requires the company to ensure that PPE:

- Is appropriate for the risks involved, without causing increases risk
- Takes account of existing conditions at place of work
- Takes account of ergonomic requirements and employees' state of health
- Fits the wearer correctly after any necessary adjustments

The type of personal protective equipment depends on the hazards to which the worker is exposed. Examples of the PPE used at Hanley Calibration Services Ltd. include:

- Eye protection
- Heat protection gloves and sleeves
- Cut resistant sleeves
- Protective footwear
- Chemical resistant glove
- Hearing protection

The Noise Regulations require an employer to take specific action at certain action values. These are the daily noise exposure level or the peak sound pressure level which, if exceeded, for an employee, action will need to be taken to reduce the risk.

These relate to: The levels of exposure to noise of your employees averaged over a working day or week and the maximum noises (peak sound pressure) to which employees are exposed in a working day.

Lower exposure action values = daily or weekly exposure of 80 dB & peak sound pressure of 135 dB;

Upper exposure action values = daily or weekly exposure of 85 dB & peak sound pressure of 137 dB.

2.20 Accident /Incident Report and Investigation

Definitions

Accident: An accident is defined as an unplanned, undesired event resulting in harm.

Incident: An incident is defined as an unplanned, undesired event that may have resulted in harm (near miss etc.)

Accident Reporting System

In the unfortunate event of an accident a set of reporting, investigating and remedial procedures are enacted:

Reporting

All employees are required to report accidents, dangerous occurrences and near miss situations to their immediate supervisor or manager. All accidents are to be reported using an **ARF-001**. The company will carry out its statutory obligation in reporting occupational accidents as required in The Management of Health and Safety at Work Regulations 1999 and report to:

Health & Safety Executive,
Incident Contact Centre,
Caerphilly Business Park,
Caerphilly,
CF83 3GG
HSE's Infoline Tel: 0845 345 0055
email: hse.infoline@natbrit.com

Investigating, Recommendations and Controls

An investigation is carried out after an accident report form is completed (ARF –001) by the Safety Officer or designee to identify the cause of the accident/incident. Copies of the report form (ARF-001) are then forwarded to the manager and safety officer. The procedures for investigating accidents are as follows:

1. Establish the facts as quickly as possible.
2. Use a camera, where possible, to take photographs of the accident scene.
3. Using sketch and take measurements of the accident scene where necessary.
4. List the names of all witnesses if possible.
5. Evaluate all the facts and determine the cause of the accident.
6. Produce a report for the responsible manager indicating the causes and recommendations to prevent a recurrence, including changes as necessary.

2.21 Pregnant Employees

Hanley Calibration will as far as possible, identify hazards in the workplace which could cause a risk to the health and safety of a pregnant woman or her new unborn child in complying with The Management of Health and Safety at Work Regulations 1999

- All female employees are encouraged to inform their manager/supervisor if they are pregnant as early as possible in the pregnancy or a new mother who is breast-feeding.
- The safety representative in liaison with the employee and their manager/supervisor will identify those aspects of work processes that will place the mother or child at risk.
- On completion of a Pregnancy Risk Assessment, all efforts are made to remove exposure to the identified risks & hazards below:
 - General Risks/Hazards Assessed:
 - Access/Egress
 - Manual Handling
 - Biological agents – including viruses, bacteria etc.
 - Stress and/or bullying
 - VDU...Ergonomics
 - Risks/Hazards specific to pregnancy
 - Pressurisation chambers
 - Rubella
 - Toxoplasma- Infection usually occurs by eating undercooked contaminated meat, exposure to cat faeces
 - Lead and lead substances

- Lead and lead substances
- Certain physically demanding tasks – heavy lifting, for instance
- The expectant and new mothers are informed about the risks and the steps taken to prevent injury to her or the unborn child.
- Every effort in terms of privacy, flexible working arrangements and facilities are made to facilitate nursing mothers.

2.22 Stress Management

Definition

Workplace stress is defined as arising “when the demands on a person exceed their capacity to meet them’ HSE (UK) Stress is a natural reaction to excessive pressure, if the stress is excessive and goes on for some time it can lead to physical and mental ill health e.g. (depression, nervous breakdown, heart disease) and loss of performance.

The causes of Workplace stress include:

- Poor communication at work
- Poorly organised shift work
- Changes at work
- Poor working relationships
- Ill-defined work roles
- Dull repetitive work
- Highly demanding tasks
- Lack of support from co-workers and others
- Excessive working hours
- Noise, poor lighting, lack of space, extreme temperatures
- Responsible jobs
- Working with the public

The Signs and Symptoms of Workplace stress include:

- Fatigue and Anxiety.
- Reduced performance and increased incidence of accidents
- High blood pressure, tension, and headaches,
- Reduced resistance to colds and other viral illnesses.
- Skin problems
- Digestive problems,
- Smoking
- Drinking alcohol
- Over eating.

Employees are encouraged to inform their manager if they are or a fellow worker is suffering from stress. Confidentially on all discussions and records of employee problems are maintained.

Management’s commitment to controlling workplace stress

The company will comply with their statutory duty under The Management of Health and Safety at Work Regulations 1999 in ensuring, as far as is reasonably practicable, the health, safety, and welfare at work of all their employees.

2.23 Bullying, Harassment & Sexual Harassment

Hanley Calibration will comply with Management of Health and Safety at Work Regulations 1999. The definitions of bullying, harassment, and sexual harassment as well as the procedures dealing with complaints about incidents of same are outlined in the EMPLOYEE HANDBOOK.

2.24 Emergency Evacuation Procedures - Fire, bomb, and any other emergency

Hanley Calibration acknowledges its responsibility in achieving a high standard of fire safety and in the provision of a safe workplace, in conforming to the requirements of The Management of Health and Safety at Work Regulations 1999. The objective of the fire safety programme is to guard against an outbreak of fire and to ensure as far as is reasonably practicable the safety of persons on the premises in the event of outbreak of fire or other emergencies, i.e., chemical spill

Training

Appropriate training in the form of notices, information and hands on experience is put in place to ensure that all employees are aware of:

Fire prevention measures

- Correct use of the provided fire-fighting equipment.
- Procedures in the event of fire or another emergency.

Fire Prevention

- Good housekeeping standards are maintained at all times.
- Electrical circuits must not be overloaded.
- Combustible materials will not be stored near heating appliance or hot surfaces.

Plan in the event of a fire or emergency:

This plan details the procedures for fire prevention and instructions in the event of a fire or other emergency as required in the Technical Guidance Document of the Building Regulations 2006. It specifies individuals' responsibilities as appropriate.

Site Evacuation:

1. On discovering a fire or other emergency situation the finder will evacuate the scene and immediately inform security of the emergency type and location. (i.e. follow site protocol)
2. When the evacuation alarm sounds all personnel will leave the site and proceed to the assembly point. Only the fire marshal (responsible person) responsible for the area may order personnel to return to the plant. (i.e. follow site protocol)

3. Risk Assessments

A Risk Assessment is defined as “An identification of hazards presents in an undertaking and an estimate of the extent of the risk involved, considering whether precautions are already being taken” The risk assessment is carried out in complying with The Management of Health and Safety at Work Regulations 1999

The risk assessment is carried out in three stages:

3.1 Identification of all hazards

- a. Liaise with client upon arrival on site or with the relevant Hanley staff member when risk assessment is in-house.
- b. Identify local site safety regulations
- c. Identify any site-specific hazards relating to work area and scope of work.
- d. Identify any other site-specific infuse., emergency exits, emergency response units, first aid stations etc

3.2 Evaluation and measurement of the risk

- a. Reference Hanley Quality System procedure DP13.
- b. For completed risk assessments see section 4 of this document

3.3 Implementation of measures to eliminate or control risks

- a. Reference Hanley Quality System procedure DP13.
- b. For completed risk assessments see section 4 of this document.

3.4 Risk and Hazard Definitions

Hazard: Is something with the potential to cause harm – substance, energy, work method, poor machinery.

Risk: Is the measure of the likelihood that the harm from a particular hazard will occur, usually expressed in quantifiable terms (i.e., Low, Med & High).

		IMPROBABLE	PROBABLE	VERY LIKELY	PROBABILITY
CRITICAL	MEDIUM	HIGH	HIGH		
MAJOR	LOW	MEDIUM	HIGH		
MINOR	LOW	LOW	MEDIUM		
	IMPACT				

3.5 Review of the risk assessment

Responsible persons in consultation with the safety representative will revise this safety statement annually and as required in accordance with legislation. Any changes in work practices, machinery, buildings, or processes will require the safety statement to be revised. The safety statement is revised as per changes in legislation or at the request of the HSE (UK). The safety officer will review all relevant safety procedures following all accident/incidents or near misses and dangerous occurrences.

NOTE: “On site” specific Risk Assessments and Method statements (RAM’s) will be developed by technicians as required and approved by the client . For completed generic risk assessments and as a guide , please see section 4 below.

4. Completed Risk Assessments

4.1 Access / Egress

Physical Hazard		Access / Egress		
HAZARD	RISKS	RISK LEVEL	CONTROLS	RISK LEVEL
Obstruction to safe access and egress of Hanley Calibrations facilities.	Injury associated with obstruction of egress for employees in the building and access for the fire brigade in the event of an obstruction.	High	Access / egress to the plant should be always kept clear and free from obstruction. All no parking zones should be appropriately marked	Medium
Unclear marking of all escape routes	Serious injury/fatality in the event of an emergency.	Medium	All obstructions are moved from blocking emergency exits	Low
Parking zones inappropriately marked	Trips, slips and falls	Low	Company's facilities are cleaned twice weekly to ensure a clean working environment is maintained	Low
Moving Vehicles next to or near pedestrians	Crush or death	high	High visibility clothing is a vital and necessary requirement in any workplace where a significant proportion of the work occurs near, in, on and around moving vehicles	Medium

4.2 Compressed Air

Chemical Hazard		Compressed Air		
HAZARD	RISKS	RISK LEVEL	CONTROLS	RISK LEVEL
Vapor's and/or liquid leakage	Drowsiness and possible asphyxiation from leaking gas	High	Safe working practiced must be adhered to as laid out in the procedure's manual.	Medium
Cylinder may explode if over-heated	Eye damage from leaking gas/Skin burns	Medium	Cylinder must not be placed near any source of heat	Low
Broken or ruptured cylinder or lines from cylinder	Death	High	Regulator and nozzle must be periodically checked and maintained to prevent leaking	Medium

4.3 Biological Agents

Chemical Hazard		Compressed Air		
HAZARD	RISKS	RISK LEVEL	CONTROLS	RISK LEVEL
Toxic or corrosive agents. Biological Agents	Hepatitis A& B	Medium	Relevant PPE must be worn. Buddy system if required. Vaccinations available on request.	Low
<p>Biological agents are widely found in the natural environment and as a result found in many work sectors.</p> <p>They include bacteria, viruses, fungi (including yeasts and moulds) and internal human parasites (endoparasites).</p> <p>In particular, severe acute respiratory syndrome coronavirus 2 (SARS-CoV-2), the virus responsible for coronavirus disease 2019 (COVID-19).</p>	<p>As they are usually invisible, it is often difficult to appreciate the risks they present. With COVID-19 an employee may be harmed by a severe acute respiratory condition, hospitalization and/or death</p>	High	<p><u>Wash hands</u> regularly and especially before eating, drinking, or smoking.</p> <p>Wash any cuts and grazes immediately with soap and running water.</p> <p>Cover any existing cuts, abrasions or breaks in the skin with waterproof dressings and/or gloves.</p> <p>Avoid hand to mouth/eye contact.</p> <p>Take rest breaks, including eating meals and taking drinks, away from potentially contaminated work areas</p> <p>Introduce Physical/Social distancing measures:</p> <ol style="list-style-type: none"> 1. Complete RAMS based on HSE advice to reduce the spread of COVID-19. 2. Erect workplace information and guidance signage. 3. Introduction of floor markings to help maintain physical distancing. 4. Provide hand sanitisers 5. Monitor & encourage social distancing between employees of 2 metres (6.5 feet) <p>Avoiding making close contact with people (i.e., do not shake hands);</p>	Medium

<p>Exposure to Biological Agent while working in a Laboratory;</p> <p>Where a risk to health or safety is caused by working with a biological agent, the Biological Agents Regulations require the Client/Customer must provide all employees at risk with suitable work clothing, special protective clothing, and PPE</p>	<p>As laboratory work activities vary greatly and different types of biological agents or materials containing biological agents may be encountered, detail cannot be given here on how to conduct specific risk assessments. In addition, different risk assessment methodologies also exist. Therefore, a general overview of the risk assessment process and a non-exhaustive list of considerations is provided.</p>	<p>High</p>	<p>Within the laboratory, various types of clothing can be used – laboratory coats, gowns, aprons, head covers, sleeve protectors/oversleeves, coveralls, full body suits, boot/shoe covers and footwear. The clothing may be designed and used for different reasons – as PPE to prevent employee harm, to prevent transfer of contamination outside the workplace or to prevent product contamination, or soiling of own clothes.</p> <p>Good Handwashing Practice should always be followed. See illustrated guide below</p>	<p>Low</p>
---	--	-------------	---	------------

How To Wash Away Germs Like A Pro



1

Wet your hands



2

Apply soap



3

Scrub hands
palm to palm



4

Scrub the back
of your hands



5

Scrub between
your fingers



6

Rub backs of
fingers against
palms



7

Clean your thumbs



8

Rub fingernails and
fingertips



9

Rinse



10

Dry hands with
paper towel



11

Turn off tap with
paper towel



12

Now your hands are
squeaky clean

4.4 Chemical Agents

Chemical Hazard		Chemical Agent		
HAZARD	RISKS	RISK LEVEL	CONTROLS	RISK LEVEL
<p>In the unlikely event of exposure to a Chemical Agent</p> <p>It is important to review the hazards associated with each specific Chemical Agent</p>	<p>Chemicals may cause health effects, for example be a respiratory sensitizer or skin irritant</p> <p>Chemicals may be a physical hazard, for example a flammable, explosive or oxidizing chemical</p> <p>Chemicals may affect the environment, if they are used, stored, or disposed of incorrectly</p>	<p>High</p>	<p>Consider what each chemical is used for, who uses it and how?</p> <p>Implement suitable control measures to eliminate or reduce the risk. Record your findings</p> <p>The Regulations enable the publication of an approved <u>Code of Practice</u> (1.4 MB) which lists occupational exposure limit values (OELV's) for about 700 chemical agents.</p> <p>Assess the risk (what is the exposure?) to employees and others Put prevention and control measures in place. Decide to deal with accidents, incidents, and emergencies. Make arrangements for information, training and consulting their employees. Provide appropriate health surveillance and keep exposure records. Supply appropriate PPE</p> <p>Chemicals classified as hazardous in accordance with Regulation (EC) No 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP) will identify chemical hazards from <u>The Label & Safety Data Sheet</u>, for industry guidance. The label on the container of a chemical agent should give information about any dangerous properties of the chemical. Read the label & act accordingly. See illustrations below:</p>	<p>Low</p>



The Safety Data Sheet must contain the following 16 headings:

1. Identification of the substance/ mixture and of the company/undertaking
2. Accidental release measures
3. Ecological information
4. Handling and storage
5. Disposal considerations
6. Hazards identification
7. Exposure controls/personal protection
8. Transport information
9. Composition/information on ingredients
10. Physical and chemical properties
11. Regulatory information
12. First aid measures
13. Stability and reactivity
14. Fire-fighting measures
15. Toxicological information
16. Other Information

4.5 Dust

Chemical Hazard		Dust		
HAZARD	RISKS	RISK LEVEL	CONTROLS	RISK LEVEL
Total Inhalable Dust – size range up to 100mm & respirable Dust – size range up to 10mm	Development of respiratory diseases, asthma	Medium	The employee should try to remove source of the dust if it is safe to do so and review OELV to determine risk over time period. An OELV (Occupational Exposure Limit Value) is defined as the limit of the time-weighted average (TWA) of the concentration of a chemical agent in the air within the breathing zone of a worker in relation to a specified reference period as approved by the Health and Safety Authority.	Low
Ignitable dusts on customers’ sites	Dry, light dusts can ignite with very low changes in temperature hence there is a risk of a fire	Medium	If it is not possible to remove the source of the dust then the employee must report it to his supervisor.	Low
Inadequacy of PPE	Inhalation of dusts due to breakthrough of the PPE	Low	If the source of dust cannot be removed or shielded, employees must wear adequate PPE such as dust masks or breathing apparatus.	Low
Process/Office Printers OELV = 0.05 – 0.2 ppm	Over exposure	Low	The masks should only be used for protection against the type of dust they are designed for.	Low

4.6 Confined Spaces

Physical Hazard		Confined Spaces		
HAZARD	RISKS	RISK LEVEL	CONTROLS	RISK LEVEL
A Confined Space is any place, including any vessel, tank, container, vat, silo, hopper, pit, bund, trench, pipe, sewer, flue, well, chamber, compartment, cellar, or other similar space which, by virtue of its enclosed nature creates conditions which give rise to a likelihood of accident, harm, or injury of such a nature as to require emergency action.	Oxygen Deficiency and/or Oxygen Enrichment Flowing Liquid or Free Flowing Solids Excessive Heat Toxic Atmosphere Flammable or Explosive Atmospheres Injury due to tripping around customer’s	High	Confined space training provided on request. Extreme care to be taken when working around customer’s equipment. Follow all safety instructions given by trained personnel on site. Do not interfere with the operations of equipment unless absolutely necessary in the course of the work and having being previously approved by the customer.	Medium

	equipment. Damage to customer's plant and equipment			
--	--	--	--	--

4.7 Electrical Installations

Physical Hazard		Electrical Installations		
HAZARD	RISKS	RISK LEVEL	CONTROLS	RISK LEVEL
Overload of electrical circuits. Damaged wiring/taped joints	Serious injury/death due to severe electric shock (electrocution)	High	All electrical equipment must be constructed, maintained, and used in a safe condition as per manufacturer's instructions	Medium
Disconnection of earth terminals/wires Damaged electrical installations and equipment	Serious burns due to electric shock if live parts are exposed	High	Damaged and frayed wiring must be immediately removed and replaced with new wiring. Any damaged electrical equipment must be tagged so as to prevent its use. All staff must report damaged equipment to their supervisor.	Medium
Use of electrical equipment in damp conditions	Increased risk if in use in damp environment	High	Extreme care must be taken when operating electrical equipment in damp and confined spaces. If an employee is unsure of the safety of a piece of equipment, he/she must consult with trained personnel	Medium

4.8 Fire

Physical Hazard		Fire		
HAZARD	RISKS	RISK LEVEL	CONTROLS	RISK LEVEL
Overload of electrical circuits	Serious injury/death due to fire	High	Electrical circuits and relays must not be overloaded	Medium
Incorrect storage of combustible materials	Injury due to explosion	High	Any material likely to cause explosion must be adequately stored and maintained so as not to overheat	Medium
Insufficient knowledge of fire evacuation procedures. Obstruction of fire exits. Misuse of emergency equipment. Inadequate regular maintenance of fire equipment	Injury/Death due to smoke inhalation	High	All employees must receive training and information on what to do in case of an emergency (induction training). All fire exits must be kept clear from obstruction at all times whether at HCS premises or on a customer's site. Emergency equipment must be only used as directed and not used for any other purpose (e.g., used as a door stop). Regular checks on fire alarm in Technology House	Medium

4.9 Housekeeping

Physical Hazard		Housekeeping		
HAZARD	RISKS	RISK LEVEL	CONTROLS	RISK LEVEL
Storage of goods above eye level	Injury due to goods toppling over and falling through weak containers	Medium	Provision of storage area that is capable of holding equipment and goods that minimizes the risk of manual handling injuries	Low
Inadequate strength of containers. Inadequate shelving Improper storage of heavy weights and hoses	Damage to goods due to inadequate strength shelves	Low	Provision of adequate strength containers to hold loose accessories and parts	Low
Untidy access-ways	Manual handling risk due to carrying heavy and awkward goods over long distances (including stairs)	Medium	All steps, stairs, floors, and passageways to be of sound construction (non-slip nature) and properly maintained (clean).	Low

4.10 Manual Materials Handling

Physical Hazard		Manual Materials Handling		
HAZARD	RISKS	RISK LEVEL	CONTROLS	RISK LEVEL
Poor lifting techniques. Lifting from confined spaces (e.g., lifting equipment from the back of his van). Lifting an unsteady load. Poor coupling (handles/grip) of load	Injury to back, feet, hands, arms due to poor posture while lifting, over reaching, and stacking	Medium	Training in manual handling is provided for all personnel for whom manual handling represents a significant part of their work to familiarise all employees with correct lifting techniques. No one is expected to lift or move a load so heavy as to cause him or her injury. Employees should not attempt to lift a load by themselves, which requires more than one person. Employees should not attempt to lift a load unless they have received manual handling training. Instructions should be given to remind employees of the proper lifting and carrying techniques. Where possible special trolleys should be available to minimise the amount of lifting.	Low

4.11 Pressure

Physical Hazard		Pressure		
HAZARD	RISKS	RISK LEVEL	CONTROLS	RISK LEVEL
Components of a customer's operation at high or low pressure e.g., nitrogen lines, high pressure tanks etc.	Pressure burns, eye injury or other injury due to exposure of material under pressure	Medium	Ensure visual inspection and cross check has been carried out on test equipment. Technicians must be fit to carry out the work on the equipment and, if required, carry a permit to work on the system.	Low
Components of Hanley Calibrations test equipment used for high-pressure calibrations	Explosion/fire due to sudden release of high-pressure materials (e.g., compressed air). Damage to equipment. Bursting of pipe work or pressure vessel	High	Take all necessary precautions to avoid coming into contact with high-pressure equipment that they are not supposed to be working on. Technicians working with a client's high-pressure equipment must consult with trained personnel to identify any risks associated with the equipment. Technicians must wear the appropriate PPE when working on high-pressure equipment (safety glasses, gloves)	Medium

4.12 Temperature

Physical Hazard		Temperature		
HAZARD	RISKS	RISK LEVEL	CONTROLS	RISK LEVEL
High temperatures when using temperature baths	Injury due to scalding/burns to the body	Medium	Avoid rapid movements to prevent splashing any hot liquid.	Low
High temperature equipment on customer's site	Injury due to scalding/burns to the body	Medium	Do not lean against or be in very close proximity to high temperature vessels on customer's sites unless absolutely necessary in the course of the work.	Low

4.13 Tools and Equipment

Physical Hazard		Tools and Equipment		
HAZARD	RISKS	RISK LEVEL	CONTROLS	RISK LEVEL
Poor tool/ equipment design	Mild injury, possible development of RSI over long period	Low	Company will ensure that all tools are suitable and safe to use for the work required	Low
Faulty/ out of specification equipment. Improper training in use of equipment	Damage to customer's equipment due to faulty tools	Low	All technicians are trained in the proper use of all tools and equipment needed to carry out the work	Low
Rotating shafts & Moving machinery, Fan Belts/Blades etc.	Entanglement/Death	High	All tools and equipment are visually inspected and tested before use. All faulty/ out of specification equipment/safety guards are to be reported to the appropriate manager and that equipment is tagged out of service until it is repaired by a qualified person or replaced. Lock out/Tag out where possible	Medium

4.14 Visual Display Equipment

Physical Hazard		Visual Display Equipment		
HAZARD	RISKS	RISK LEVEL	CONTROLS	RISK LEVEL
Computer display screens	Postural problems. Visual problems. Fatigue and stress from prolonged use	Low	Ensure screen is positioned correctly to reduce glare from light sources (window and additional lighting). Take frequent breaks when working at a VDU to reduce the onset of fatigue. Regular maintenance of the equipment to repair flickering or other faults which can damage the eyes. Provision of anti-glare screen if requested by employee. Good ergonomic positioning, feet flat on the ground, back straight. Provision of footrest if requested by employee. Provision of wrist support for prolonged use of keyboard to reduce the effects of RSI's and carpal tunnel syndrome	Low

4.15 Noise

Physical Hazard		Noise		
HAZARD	RISKS	RISK LEVEL	CONTROLS	RISK LEVEL
<p>Sound pressure levels greater than the occupational exposure limit of 80 dB (A) (Equivalent to not being able to hear normal conversation at a distance of 2 metres)</p>	<p>Risk of developing noise induced hearing loss (NIHL) due to noisy environments.</p> <p>Developing stress/ noise related headaches as well as increased fatigue</p> <p>There are two action values: Lower exposure action values: LEX,8h = 80 dB (A) & peak = 135 dB (C)</p> <p>Upper exposure action values: LEX,8h = 85 dB (A) & peak = 137 dB (C)</p>	<p>Medium</p>	<p>Information to be provided to all staff detailing the risks of exposure to noise > 80 dB (A) first action level. The source of the noise should be removed if possible.</p> <p>If this is not possible then engineering controls must be used. These would include shielding/enclosing the source with an absorbing material, creating a large as possible distance between the employee and the source. (The intensity falls off inversely with distance).</p> <p>PPE should only be used as a last resort. Earplugs and ear defenders should be constructed of a material that is suitable to provide adequate protection against the sound.</p>	<p>Low</p>

4.16 Working from Home and Temporary Workstations

Physical Hazard		Working from Home and Temporary Workstations		
HAZARD	RISKS	RISK LEVEL	CONTROLS	RISK LEVEL
Poor Ergonomic set up	Postural problems. Back & Shoulder pain. Fatigue & soreness of the eyes	Medium	Ergonomic Risk Assessment form: WFH RA 01 Keep feet flat on the ground, back straight. Provision of footrest and follow the guide in the Employee Handbook . Ensure screen is positioned correctly to reduce glare from light sources (window and additional lighting)	Low
Loneliness & lack of human interaction	Mental Health Issues & stress related illness	Medium	Take frequent breaks. Maintain constant communication with your manager and speak out if any issues or problems	Low
Electrical Cables	Trips, slips & falls	Medium	Reduce clutter and exercise good house keeping	Low
Poor Time Management	Tiredness, fatigue & poor motivation	Medium	Limit your screen time and switch off at end of each working day, ensuring your schedule coincide with those in your team for as long as is necessary to complete duties effectively. Define your boundaries between working time & family time	Low
Distractions from working in a shared environment; (family, children, pets etc.)	Mental Health Issues & stress related illness	High	If working from home is not suitable or compatible to your home set-up, please make your manager aware and alternative arrangements will be arranged, for example: hire a hot desk in local business hub.	Low

5. References

- Health and Safety at Work Act 1974,
- The Fire Precautions (Workplace) Regulations 1997,
- The Management of Health and Safety at Work Regulations 1999
- Hanley Calibration Quality Management System procedure DP13 Risk Management
- Hanley Calibration Quality Management System procedure DP9 Training and Recruitment
- Hanley Calibration Quality Management System procedure DP6 On site operations
- Hanley Calibration Employee Handbook:
 - Working from Home Policy
 - Driving for Work Policy